

## PRIMO PREMIUM

### Homogeneous Compact Vinyl

- Non directional, no wax, no polish for life homogeneous flooring solutions.
- Highest abrasion performance with Class T wear classification.
- Made in Sweden and comes with multicolour welding rods.
- Extremely low VOC emission of  $\leq 10\mu\text{g}/\text{m}^3$  indoor air quality.

Technical Data Sheet



THE ULTIMATE  
FLOORING EXPERIENCE





# PRIMO PREMIUM

## Technical Data

CERTIFICATION & CLASSIFICATION	STANDARDS	PRIMO PREMIUM
Classification	ISO 10581 ISO 11638 EN 13845 EN ISO 10874	Homogeneous vinyl flooring - - 34-43
Wear layer binder content	ISO 10581 ISO 11638	Type I -
TECHNICAL CHARACTERISTICS	STANDARDS	PRIMO PREMIUM
Total thickness	ISO 24346 EN 428	2.00 mm
Total weight	ISO 23997 EN 430	3000 g/m <sup>2</sup>
Wear layer thickness	ISO 24340 EN 429	-
Foam layer thickness	EN ISO 24340	-
Adhesive foil thickness	EN ISO 24340	-
Surface treatment	-	PUR reinforced
Abrasion group	EN 660-2	Group T: ≤ 2.00 mm <sup>3</sup>
Form of delivery	EN ISO 24341 Sheet (rolls)	Approx. 23 lm x 200 cm Art. no. 21010 ___ 3 digit colour number
	EN ISO 24342 Tiles (box)	61 x 61 cm - 16 tiles/box = 5.95 m <sup>2</sup> Art. no. 21011 ___ 3 digit colour number
TECHNICAL PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)	STANDARDS	PRIMO PREMIUM
Declaration of Performance	EN 14041	0019-0020-DoP-2013-07
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B <sub>fl</sub> s1 ≥ 8 kW/m <sup>2</sup> Pass
Static electrical charge	EN 1815	< 2 kV
Thermal resistance	EN 12667/DIN 52612	Approx 0.01m <sup>2</sup> K/W
Slip resistance	EN 13893 BS 7976-2	≥ 0.3 Low risk of slip
TECHNICAL PERFORMANCES	STANDARDS	PRIMO PREMIUM
Residual indentation	EN ISO 24343-1	Required value: ≤ 0.10 mm Best measured value*: 0.03 mm
Impact sound reduction	EN ISO 717/2	-
Slip resistance	DIN 51130	R9
Clean room test	ASTM F24 F51 ISO 14644-1	Class A ISO class 4
Ease of decontamination	ISO 8690	Good
Bacteria resistance	EN ISO 846: Part C	Does not favour growth
Chemical resistance	ISO 26987	Good resistance
Castor wheel test	ISO 4918	Suitable
Flexibility	ISO 24344	Pass
Dimensional stability	ISO 23999	Rolls : ≤ 0.40% ≤ 0.25 % for tiles
Light fastness	EN ISO 105-B02	≥ Level 6
Electrical insulation	VDE 0100, Part 600	-
Electrical resistance	EN 1081	-
Bare foot test	DIN 51097	-
Seam strength	EN 684	-
Underfloor heating	DIN 52612	Individual values: ≥ 400 N/50 mm Suitable-max. 27°C
ENVIRONMENTAL PERFORMANCES	STANDARDS	PRIMO PREMIUM
Total VOC emissions	ISO 16000-9 Indoor air quality	≤ 10 µg/m <sup>3</sup> (after 28 days) Platinum
COLOURS	STANDARDS	PRIMO PREMIUM
		36

The above information is subject to modification for the benefit of further improvement. (05/16)  
Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

CUSTOMS TARIFF: 48205000000F



**Ahmadabad:**

Surface Plus, GF, 4th Floor  
Premier House, Opp. Gurudwara  
Thaltej Crossing, Ahmadabad – 382 454  
Tel: +91 79 4006 0521 / 79 2685 3312  
Email: ahmadabad@squarefoot.co.in

**Bengaluru:**

#51, 1st Floor, 100 Feet Road  
4th Block, Koramangala  
Bengaluru – 560 034  
Tel: +91 80 4110 1012 / 13  
Fax: +91 80 2563 3145  
Email: bangalore@squarefoot.co.in

**Chennai:**

#96, 3rd Floor, Opp. Vani Mahal  
G. N. Chetty Road, T. Nagar  
Chennai – 600 017  
Tel: +91 44 4550 8411 / 12  
Email: chennai@squarefoot.co.in

**Goa:**

403, 4th Floor, Gera Imperium  
1st Building, Behind KTC Bus Stand  
Patto Plaza, Panjim, Goa – 403 001  
Tel: +91 832 243 7663  
Email: goa@squarefoot.co.in

**Hyderabad:**

6 – 3 – 354/1, 2nd Floor, Stellar Sphinx  
Panjagutta Main Road, Road No. 1  
Banjara Hills, Hyderabad – 500 034  
Tel: +91 40 4003 7212 / 13  
Fax: +91 40 4003 7214  
Email: hyderabad@squarefoot.co.in

**Indore:**

154, 1st Floor Orbit Mall, A.B. Road  
Indore – 452 001  
Tel: +91 731 498 1983  
Email: indore@squarefoot.co.in

**Jaipur:**

2nd Floor, Plot No. 287, Vaishali Marg  
Gomes Defence Colony, Opp. Ktl Maruti Showroom  
Near Big Bazaar, Jaipur, Rajasthan – 302 021  
Tel: +91 141 492 2396  
Email: jaipur@squarefoot.co.in

**Kochi:**

2nd Floor Chakrampilly Estate  
NH Bypass, Palarivattom  
Thammanam PO, Cochin  
Kerala – 682 032. (Opp: Holiday Inn)  
Tel: +91 484 485 6173  
Email: kochi@squarefoot.co.in

**Kolkata:**

#332, Homeland Mall  
18B, Ashuthosh Mukherjee Road  
Kolkata – 700 020  
Tel: +91 33 2455 4344  
Email: kolkata@squarefoot.co.in

**Mumbai:**

9–11 Senapati Bapat Marg  
Lower Parel, Mumbai – 400 013  
Tel: +91 22 4047 6211  
Fax: +91 22 2497 6216

**New Delhi:**

M – 56, 2nd Floor, M–Block Market  
Greater Kailash Part II  
New Delhi – 110 048  
Tel: +91 11 4052 5767 / 11 4050 4785  
Email: delhi@squarefoot.co.in

**Pune:**

Classic Floorings & Interiors Pvt Ltd,  
Office No. 201, 2nd Floor, Gagan Capital  
Dhole Patil Road, Beside Ruby hall Clinic Exit Gate,  
Landmark – Above Anna Idly & CCD  
Pune – 411 001  
Tel: +91 20 4000 1630  
Email: pune@squarefoot.co.in

**Area Representatives**

Bhopal	+91 82913 17558
Bhubaneshwar	+91 96742 23380
Coimbatore	+91 90032 56718
Guwahati	+91 96749 93005
Nasik	+91 86575 03355
Patna	+91 98363 11556
Surat	+91 97237 77887

**Head Office:**

Classic Floorings & Interiors (P) Ltd., Ground Floor, Raghuvanshi Mansion  
Raghuvanshi Mills Compound, 9–11 Senapati Bapat Marg, Lower Parel, Mumbai – 400 013. Tel: +91 22 4047 6211 | Fax: +91 22 2497 6216

Toll Free: 1800 226 211 ■ sales@squarefoot.co.in ■ www.squarefoot.co.in