



TORO SC

Static Control Flooring

- Permanently conductive flooring with carbon or black backing.
- VOC emissions 10 times lower than the strictest standards in Europe.
- Economical ESD Flooring with best in class functional performance.
- Static control floorings for highly technical areas.
- 100% recyclable.

[Technical Data Sheet](#)



THE ULTIMATE
FLOORING EXPERIENCE



TORO SC

Technical Data

CERTIFICATION & CLASSIFICATION	STANDARDS	TORO SC
Type of floor covering	ISO 10582 - (EN 649)	Permanently static conductive pressed homogeneous vinyl with carbon backing
Binder content	ISO 10581	Type I
CE Certification	EN 14041	Yes
Classification	ISO 10581 - (EN 649)	Commercial: 34 Industrial: 43
ISO Certification		Ronneby ISO 9001/Ronneby ISO 14001
CERTIFICATION & CLASSIFICATION	STANDARDS	TORO SC
PUR		Yes
Total Thickness	ISO 24346 - EN 428	2.0 mm
Wear Layer Thickness	ISO 24340 – EN 429	2.0 mm
Total Weight /m ²	ISO 23997 - EN 430	2950 g
Form of delivery	ISO 24341 - EN 426	Approx. 23 running metres x 200 cm
CERTIFICATION & CLASSIFICATION	STANDARDS	TORO SC
Dimensional Stability	ISO 23999 - EN 434	≤ 0,40 % for rolls ≤ 0,25 % for tiles
Reaction to fire	EN 13501-1 EN ISO 9239 -1 EN ISO 11925 - 2	Class B _{fl} s1 ≥ 8 kW/m ² Pass
Abrasion volume loss	EN 660: Part 2	Group P: ≤ 4,0 mm ³
Residual indentation	ISO 24343-1 - EN 433	Approx. 0,02 mm
Castor chair test	ISO 4918 - EN 425	Suitable
Flexibility	ISO 23344 EN 435	Pass
Static electric charge	EN 1815	< 2 kV
Ease of decontamination	ISO 8690	Excellent
Electrical insulation	VDE 100, Part 600	R _i ≤ 5x10 ⁴ Ohms
Electrical resistance	ESD-approval SP method 2472 EN 1081 EN/IEC 61340-4-1, 100 V EN/IEC 61340-4-5	R ≤ 10 ⁸ Ohms R ₁ 5x10 ⁴ ≤ R ≤ 10 ⁶ Ohms R ₂ 5x10 ⁴ ≤ R ≤ 10 ⁶ Ohms R 5x10 ⁴ ≤ R ≤ 10 ⁶ Ohms ≤ 3,5 x 10 ⁷ Ohms
Total VOC emissions	ISO 16000-6 AgBB/ DIBt Indoor air quality FloorScore	≤ 10 µg/m ³ (after 28 days) Confirm Platinum SCS certified
Underfloor heating		Suitable – max 27°C
Thermal resistance	EN ISO 10456 (EN 12524)	Approx. 0,01 m ² K/W
Light fastness	EN ISO 105 - B02	≥ level 6
Chemical resistance	ISO 26987 – EN 423	Excellent
Clean room	ISO 14644 - 1 ASTM F24 F51	ISO class 4 Class A
Bacteria resistance	DIN EN 846 Part C	Does not favour growth
Slip resistance	DIN 51130 EN 13893	R9 ≥ 0.3
Seam strength	EN 684	Average value: ≥ 240 N/50 mm Individual values: ≥ 180 N/50 mm

The above mentioned information is subject to modification for the benefit of further improvement

iQ Toro SC



Data is subject to change.

Ahmadabad:

Surface Plus, GF, 4th Floor
Premier House, Opp. Gurudwara
Thaltej Crossing, Ahmadabad – 382 454
Tel: +91 79 4006 0521 / 79 2685 3312
Email: ahmadabad@squarefoot.co.in

Bengaluru:

#51, 1st Floor, 100 Feet Road
4th Block, Koramangala
Bengaluru – 560 034
Tel: +91 80 4110 1012 / 13
Fax: +91 80 2563 3145
Email: bangalore@squarefoot.co.in

Chennai:

#96, 3rd Floor, Opp. Vani Mahal
G. N. Chetty Road, T. Nagar
Chennai – 600 017
Tel: +91 44 4550 8411 / 12
Email: chennai@squarefoot.co.in

Goa:

403, 4th Floor, Gera Imperium
1st Building, Behind KTC Bus Stand
Patto Plaza, Panjim, Goa – 403 001
Tel: +91 832 243 7663
Email: goa@squarefoot.co.in

Hyderabad:

6 – 3 – 354/1, 2nd Floor, Stellar Sphinx
Panjagutta Main Road, Road No. 1
Banjara Hills, Hyderabad – 500 034
Tel: +91 40 4003 7212 / 13
Fax: +91 40 4003 7214
Email: hyderabad@squarefoot.co.in

Indore:

154, 1st Floor Orbit Mall, A.B. Road
Indore – 452 001
Tel: +91 731 498 1983
Email: indore@squarefoot.co.in

Jaipur:

2nd Floor, Plot No. 287, Vaishali Marg
Gomes Defence Colony, Opp. Ktl Maruti Showroom
Near Big Bazaar, Jaipur, Rajasthan – 302 021
Tel: +91 141 492 2396
Email: jaipur@squarefoot.co.in

Kochi:

2nd Floor Chakrampilly Estate
NH Bypass, Palarivattom
Thammanam PO, Cochin
Kerala – 682 032. (Opp: Holiday Inn)
Tel: +91 484 485 6173
Email: kochi@squarefoot.co.in

Kolkata:

#332, Homeland Mall
18B, Ashuthosh Mukherjee Road
Kolkata – 700 020
Tel: +91 33 2455 4344
Email: kolkata@squarefoot.co.in

Mumbai:

9–11 Senapati Bapat Marg
Lower Parel, Mumbai – 400 013
Tel: +91 22 4047 6211
Fax: +91 22 2497 6216

New Delhi:

M – 56, 2nd Floor, M–Block Market
Greater Kailash Part II
New Delhi – 110 048
Tel: +91 11 4052 5767 / 11 4050 4785
Email: delhi@squarefoot.co.in

Pune:

Classic Floorings & Interiors Pvt Ltd,
Office No. 201, 2nd Floor, Gagan Capital
Dhole Patil Road, Beside Ruby hall Clinic Exit Gate,
Landmark – Above Anna Idly & CCD
Pune – 411 001
Tel: +91 20 4000 1630
Email: pune@squarefoot.co.in

Area Representatives

Bhopal	+91 82913 17558
Bhubaneshwar	+91 96742 23380
Coimbatore	+91 90032 56718
Guwahati	+91 96749 93005
Nasik	+91 86575 03355
Patna	+91 98363 11556
Surat	+91 97237 77887

**Head Office:**

Classic Floorings & Interiors (P) Ltd., Ground Floor, Raghuvanshi Mansion
Raghuvanshi Mills Compound, 9–11 Senapati Bapat Marg, Lower Parel, Mumbai – 400 013. Tel: +91 22 4047 6211 | Fax: +91 22 2497 6216

Toll Free: 1800 226 211 ■ sales@squarefoot.co.in ■ www.squarefoot.co.in