




VENETO XF2

Technical Data Sheet



THE ULTIMATE FLOORING EXPERIENCE



VENETO XF2

Technical Data

CERTIFICATION & CLASSIFICATION	STANDARDS	Veneto xl TM 7 mm	Veneto xl TM Style Estmo xl TM Style Elmo xl TM Trentino xl TM Ondale xl TM 1,5 mm	Lineum xl TM Bx 2,5 mm	Originale Essenza Veneto	Veneto Sicuro xl TM 2,5 mm	Etrusco xl TM 2,5 mm	Lineum Conductive xl TM 2,5 mm	Lineum SD Static Dissipative xl TM 2,5 mm	Veneto xl TM 3,5 mm	Stiloso xl TM 3,5 mm	Veneto Acoustic Cork xl TM 4,4 mm	Onale xl TM 2 mm
ISO 24011 (EN 548)		One single-layer calendared linoleum on jute backing											
Type of floor covering	EN 686	-	-	-	-	-	-	-	-	-	-	-	-
	EN 687	-	-	-	-	-	-	-	-	-	-	-	-
CE certification	EN 14041	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Classification	EN ISO 10874 Domestic Commercial Light Industrial	Classes: 23 23 41	Classes: 23 23 43	Classes: 23 23 43	Classes: 23 23 43	Classes: 23 23 43	Classes: 23 23 43	Classes: 23 23 43	Classes: 23 23 43	Classes: 23 23 43	Classes: 23 23 43	Classes: 23 23 43	Classes: 23 23 43
TECHNICAL CHARACTERISTICS	STANDARDS	xl TM	xl TM	xl TM	Essenza	xl TM	xl TM	xl TM	xl TM	xl TM	xl TM	xl TM	xl TM
Surface treatment	EN ISO 24346	2,0 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,0 mm
Total thickness	EN ISO 23997	ca. 2.400 g/m ²	ca. 3.000 g/m ²	ca. 3.200 g/m ²	ca. 3.000 g/m ²	ca. 3.000 g/m ²	ca. 3.000 g/m ²	ca. 3.000 g/m ²	ca. 3.000 g/m ²	ca. 3.900 g/m ²	ca. 3.450 g/m ²	ca. 4.600 g/m ²	ca. 2.900 g/m ²
Residual indentation	EN ISO 24343-1 Standard requirements Best measured value	≤ 0,15 mm ca. 0,07 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,20 mm	≤ 0,15 mm ca. 0,20 mm	≤ 0,40 mm ca. 0,20 mm	-
Flexibility	EN ISO 24344 Method A	≤ 25 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 40 mm Ø	-
Form of delivery	EN ISO 24341	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m or ≤ 32 x 1,95 m (subject to availability-by-phase check upon order)	≤ 16 x 2 m
TECHNICAL PERFORMANCE	STANDARDS												
Fire classification	EN 13501-1	Cp+1	Cp+1	Bp+1	Cp+1	Cp+1	Cp+1	Bp+1	Cp+1	Cp+1	Cp+1	Cp+1	B+1
Fire efficient toxicity	ISO 9697-2 evaluation according to EN 60545-2 Annex C1	-	-	-	-	-	-	-	-	-	-	-	-
Impact sound reduction	EN ISO 10140-3/EN ISO 717-2	5 dB	6 dB	6 dB	6 dB	6 dB	6 dB	6 dB	6 dB	8 dB	10 dB	15 dB	-
Impact sound in the room	NF S31-074	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class B < 75 dB	Class A < 65 dB	Class B < 75 dB	-
Impact sound reduction with Eufono®	EN ISO 10140-3/EN ISO 717-2	14 dB	14 dB	14 dB	14 dB	14 dB	14 dB	14 dB	14 dB	Not applicable	15 dB	Not applicable	-
Castor chair	EN ISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)											
Static electrical propensity	EN 1815	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV
Electrical resistance	EN 1081	-	-	-	-	-	-	-	-	R1 ≤ 10 ¹⁰ Ω	R1 ≤ 10 ¹⁰ Ω	-	-
	ESD-approval SP method 2472	-	-	-	-	-	-	-	-	R2 ≤ 10 ¹⁰ Ω	R2 ≤ 10 ¹⁰ Ω	-	-
	EN IEC 61340-4	-	-	-	-	-	-	-	-	R ≤ 10 ¹⁰ Ω	R ≤ 10 ¹⁰ Ω	-	-
Impact resistance	EN 259-2	-	-	-	-	-	-	-	-	-	-	-	Resistant to impacts
Slip resistance	EN 13893 DIN 51130	DS ≥ 0,30 RP	DS ≥ 0,30 RP	DS ≥ 0,30 RP	DS ≥ 0,30 RP	DS ≥ 0,30 RP	DS ≥ 0,30 RP	DS ≥ 0,30 RP	DS ≥ 0,30 RP	DS ≥ 0,30 RP	DS ≥ 0,30 RP	DS ≥ 0,30 RP	DS ≥ 0,30 RP
Chemical resistance	EN ISO 26987	Resistant to dilute acids, alkalis, current solvents and alcohols											
Thermal resistance Underfloor heating	EN ISO 10456	0,012 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,019 m ² K/W Suitable	0,019 m ² K/W Suitable	0,045 m ² K/W Suitable	0,018 m ² K/W Suitable
Light fastness	EN ISO 105-B02	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6
Presence of phthalate compounds	CEN ISO/TS 16181	Phthalate free											
Odor test requirement of emission class M1	EN 14002	Meets requirement											
Spottability, washability and extra washability	EN 12856 EN 233	Meets requirement											
Determination of antibacterial activity	ISO 22196	Naturally bactericidal (Bacteria mix - E-Coli and MRSA)						Naturally bactericidal (Bacteria mix - E-Coli and MRSA)					
Colours		19	60 (Veneto) 13 (Style Estmo) 8 (Style Elmo) 10 (Trentino) ON REQUEST: 3 (Originale Vegetale) 3 (Originale Minerale) 10 (Trentino B-I)	29 (Veneto) 13 (Style Estmo) 8 (Style Elmo) 3 (Originale Vegetale) 3 (Originale Minerale) 10 (Trentino B-I)	ON REQUEST: 60 (Veneto)	16	1	3	9	27 (Veneto) 8 (Style Estmo) 1 (Style Elmo) 3 (Trentino) ON REQUEST: 10 (Trentino)	ON REQUEST: 60 (Veneto)	6	

The above information is subject to modification for the benefit of further improvement. (01/21)

CUSTOMS TARIFF: 482050000000F

DISCLAIMER: Although the utmost care is taken, the data here given could differ and be subject to modifications from a technical point of view. This sheet is intended for information purposes only. It does not constitute an offer or any other legal document. Please check the effective availability of the products presented at the time of order. Due to the technical limits of reproduction and printing techniques used, the appearance (color) of the product may vary from the samples, panels or other visual display materials exhibited to the customer. It is mandatory to have the products installed properly if they are to be service comply and safely. Refer to Tarkett technical installation and maintenance directions, available at www.tarkett.com or at your Tarkett dealer. *Eufono: 20mm traditional 100% natural cork underlayment to be installed in combination with any compact Tarkett linoleum to get additional sound reduction up to 15dB, depending on the product. Available in rolls 32m x 2m.



Acoustic Cork	93% Sound Absorption	100% Phthalate Free	100% Formaldehyde Free	100% VOC AT 28 DAY
Conductive	96% Sound Absorption	100% Phthalate Free	100% Formaldehyde Free	100% VOC AT 28 DAY
Eufono	100% Sound Absorption	100% Phthalate Free	100% Formaldehyde Free	100% VOC AT 28 DAY
Etrusco	93% Sound Absorption	100% Phthalate Free	100% Formaldehyde Free	100% VOC AT 28 DAY
Originale	99% Sound Absorption	100% Phthalate Free	100% Formaldehyde Free	100% VOC AT 28 DAY
SD	98% Sound Absorption	100% Phthalate Free	100% Formaldehyde Free	100% VOC AT 28 DAY
Silencio	83% Sound Absorption	100% Phthalate Free	100% Formaldehyde Free	100% VOC AT 28 DAY
Style	96% Sound Absorption	100% Phthalate Free	100% Formaldehyde Free	100% VOC AT 28 DAY
Trentino	94% Sound Absorption	100% Phthalate Free	100% Formaldehyde Free	100% VOC AT 28 DAY
Veneto	94% Sound Absorption	100% Phthalate Free	100% Formaldehyde Free	100% VOC AT 28 DAY

SUSTAINABILITY

Tarkett was the first linoleum flooring manufacturer to be Cradle to Cradle® certified - underlining our strong commitment to sustainability.

Product certifications



International certifications



Factory certifications



All our Linoleum products are eligible for LEED v4 credits. For more information: <http://www.c2certified.org/products/registry>

Data is subject to change.

Ahmadabad:

Surface Plus, GF, 4th Floor
Premier House, Opp. Gurudwara
Thaltej Crossing, Ahmadabad – 382 454
Tel: +91 79 4006 0521 / 79 2685 3312
Email: ahmadabad@squarefoot.co.in

Bengaluru:

#51, 1st Floor, 100 Feet Road
4th Block, Koramangala
Bengaluru – 560 034
Tel: +91 80 4110 1012 / 13
Fax: +91 80 2563 3145
Email: bangalore@squarefoot.co.in

Chennai:

#96, 3rd Floor, Opp. Vani Mahal
G. N. Chetty Road, T. Nagar
Chennai – 600 017
Tel: +91 44 4550 8411 / 12
Email: chennai@squarefoot.co.in

Goa:

403, 4th Floor, Gera Imperium
1st Building, Behind KTC Bus Stand
Patto Plaza, Panjim, Goa – 403 001
Tel: +91 832 243 7663
Email: goa@squarefoot.co.in

Hyderabad:

6 – 3 – 354/1, 2nd Floor, Stellar Sphinx
Panjagutta Main Road, Road No. 1
Banjara Hills, Hyderabad – 500 034
Tel: +91 40 4003 7212 / 13
Fax: +91 40 4003 7214
Email: hyderabad@squarefoot.co.in

Indore:

154, 1st Floor Orbit Mall, A.B. Road
Indore – 452 001
Tel: +91 731 498 1983
Email: indore@squarefoot.co.in

Jaipur:

2nd Floor, Plot No. 287, Vaishali Marg
Gomes Defence Colony, Opp. Ktl Maruti Showroom
Near Big Bazaar, Jaipur, Rajasthan – 302 021
Tel: +91 141 492 2396
Email: jaipur@squarefoot.co.in

Kochi:

2nd Floor Chakrampilly Estate
NH Bypass, Palarivattom
Thammanam PO, Cochin
Kerala – 682 032. (Opp: Holiday Inn)
Tel: +91 484 485 6173
Email: kochi@squarefoot.co.in

Kolkata:

#332, Homeland Mall
18B, Ashuthosh Mukherjee Road
Kolkata – 700 020
Tel: +91 33 2455 4344
Email: kolkata@squarefoot.co.in

Mumbai:

9–11 Senapati Bapat Marg
Lower Parel, Mumbai – 400 013
Tel: +91 22 4047 6211
Fax: +91 22 2497 6216

New Delhi:

M – 56, 2nd Floor, M–Block Market
Greater Kailash Part II
New Delhi – 110 048
Tel: +91 11 4052 5767 / 11 4050 4785
Email: delhi@squarefoot.co.in

Pune:

Classic Floorings & Interiors Pvt Ltd,
Office No. 201, 2nd Floor, Gagan Capital
Dhole Patil Road, Beside Ruby hall Clinic Exit Gate,
Landmark – Above Anna Idly & CCD
Pune – 411 001
Tel: +91 20 4000 1630
Email: pune@squarefoot.co.in

Area Representatives

Bhopal	+91 82913 17558
Bhubaneshwar	+91 96742 23380
Coimbatore	+91 90032 56718
Guwahati	+91 96749 93005
Nasik	+91 86575 03355
Patna	+91 98363 11556
Surat	+91 97237 77887

**Head Office:**

Classic Floorings & Interiors (P) Ltd., Ground Floor, Raghuvanshi Mansion
Raghuvanshi Mills Compound, 9–11 Senapati Bapat Marg, Lower Parel, Mumbai – 400 013. Tel: +91 22 4047 6211 | Fax: +91 22 2497 6216

Toll Free: 1800 226 211 ■ sales@squarefoot.co.in ■ www.squarefoot.co.in