

Laminate Wood Floors | Engineered Wood Floors | Solid Wood Floors | Design Wood Floors | Outdoor Wood Floors | Vinyl Floors | Sports Floors | Carpets

## Preventive Maintenance

- 1. Use NON–RUBBER protective mats in front of any doors leading to the outside. This helps keep the sand and grit from getting on to your floors. Gritty sand is any floor covering's worst enemy.
- 2. Install proper floor protectors (felt preferred) on all furniture legs used on resilient flooring. Protectors will allow chairs to move easily over the floor without scuffing or scratching. Clean protectors on a regular basis to remove any grit that may have become embedded on the bottom of the furniture leg. For any swiveled type office chairs and other rolling furniture, please install 5 cm wide non-staining flat casters. Do not use rubber casters.
- **3.** To keep your floor looking its best, dust mop or vacuum your floor at least twice a week. Do it more often on floors with heavy traffic. Do not use a household dust cleaner of any kind as this may cause the floor to become slick or damage the finish. Simply sweep the floor as often as needed.
- 4. Do not allow pets with unclipped nails to damage your SPC Structure floor. It may result in severe scratching to the surface. The same is true for any high heeled shoes that do not have proper tips on the heels.
- 5. Avoid exposure to direct sunlight for prolonged periods of time. During peak sunlight hours, use drapes or blinds to minimize the direct sunlight on the SPC Structure floor. Most types of flooring will be affected by continuous strong sunlight. To avoid an uneven appearance, please consider relocations of any area rugs from time to time. In addition, excessive temperatures are not good for resilient floors. Some natural ventilation or intermittent air conditioning in vacant homes should be considered. Long term continuous inside temperatures over 35°C combined with strong direct sunlight will damage your SPC Structure floor and cause the installation to fail.
- 6. Do NOT use a steam cleaner on SPC Structure flooring as it may result in permanent damage to your floor and will void the warranty.

#### **HELPFUL HINT 7:**

SPC Maintenance Guide

To avoid yellowing from asphalt driveways or parking lots, always use doormats at entranceways. It's a good idea to use a hard surface floor attachment when vacuuming your SPC Structure floor.

# Regular Maintenance

- 1. Food spills should be cleaned up as rapidly as possible with a quality liquid vinyl cleaner. Make sure the cleaner you choose is an allpurpose liquid cleaner that is NON–ABRASIVE. We do not recommend powdered cleaners, oil soaps, dishwashing detergents, or other dusting products. Try to use a non–rinsing, biodegradable cleaner that leaves no residue or haze and requires no rinsing after application.
- 2. Shoe marks and scuffs can be easily removed using a spot application of your non–abrasive cleaner and a green Scotch Brite pad.
- 3. Regular household dirt can be cleaned with a neutral vinyl cleaner applied as indicated on the products label. Some hand wiping maybe required to remove tough spots and spills. Always sweep or vacuum your SPC Structure floor before cleaning so that all loose dirt and particles are removed. For best results do not use combination cleaner/ finish products.
- 4. Do NOT WAX YOUR SPC STRUCTURE FLOOR! The surface of your SPC Structure floor is very dense and non-porous; this prevents wax from penetrating and thus will build up a bed for yellowing and dirt collection. The same non-porous feature also provides all the protection against wear and staining that you will need.
- 5. If your floor has been exposed to excessive amounts of water due to flooding, don't panic, SPC Structure is waterproof! Simply remove the water as quickly as possible with a Wet–Vac or other device and ventilate the room. A dehumidifier should be promptly turned on in the room to reduce the moisture levels back to normal. Do not dry the room below the normal moisture level that existed previously.
- If accidental deep scratches appear on your floor then it might be necessary to replace such damaged planks.
- 7. If the scratches are fine and the result of normal household use, then it is recommended only to fill them with one or two coats of a matte floor finish.

## Ahmadabad:

Surface Plus, GF, 4th Floor Premier House, Opp. Gurudwara Thaltej Crossing, Ahmadabad – 382 454 Tel: +91 79 4006 0521 / 79 2685 3312 Email: ahmadabad@squarefoot.co.in

#### **Bengaluru:**

#51, 1st Floor, 100 Feet Road 4th Block, Koramangala Bengaluru – 560 034 Tel: +91 80 4110 1012 / 13 Fax: +91 80 2563 3145 Email: bangalore@squarefoot.co.in

## Chennai:

#96, 3rd Floor, Opp. Vani Mahal G. N. Chetty Road, T. Nagar Chennai – 600 017 Tel: +91 44 4550 8411 / 12 Email: chennai@squarefoot.co.in

## Goa:

605, 6th Floor, Gera Imperium 1st Building, Behind KTC Bus Stand Patto Plaza, Panjim, Goa – 403 001 Tel: +91 832 243 7663 Email: goa@squarefoot.co.in

#### Hyderabad:

6 – 3 – 354/1, 2nd Floor, Stellar Sphinx Panjagutta Main Road, Road No. 1 Banjara Hills, Hyderabad – 500 034 Tel: +91 40 4003 7212 / 13 Fax: +91 40 4003 7214 Email: hyderabad@squarefoot.co.in

## Indore:

154, 1st Floor Orbit Mall, A.B. Road Indore – 452 001 Tel: +91 731 498 1983 Email: indore@squarefoot.co.in

#### Jaipur:

2nd Floor, Plot No. 287, Vaishali Marg Gomes Defence Colony, Opp. Ktl Maruti Showroom Near Big Bazaar, Jaipur, Rajasthan – 302 021 Tel: +91 141 492 2396 Email: jaipur@squarefoot.co.in

## Kochi:

2nd Floor Chakrampilly Estate NH Bypass, Palarivattom Thammanam PO, Cochin Kerala – 682 032. (Opp: Holiday Inn) Tel: +91 484 485 6173 Email: kochi@squarefoot.co.in

#### Kolkata:

34, Dr. Sarat Banerjee Road BSNL Telephone Exchange Lane Police Station Rabindra Sarobar Kolkata – 700 029 Tel: +91 33 4060 4243 Email: kolkata@squarefoot.co.in

## Mumbai:

9–11 Senapati Bapat Marg Lower Parel, Mumbai – 400 013 Tel: +91 22 4047 6211 Fax: +91 22 2497 6216

## **New Delhi:**

A-31, Ground Floor FIEE Complex, Okhla Phase-II New Delhi - 110 020 Tel: +91 11 4052 5767 / 11 4050 4785 Email: delhi@squarefoot.co.in

## Pune:

Classic Floorings & Interiors Pvt Ltd, Office No. 201, 2nd Floor, Gagan Capital Dhole Patil Road Beside Ruby Hall Clinic Exit Gate Landmark – Above Anna Idly & CCD Pune – 411 001 Tel: +91 20 4000 1630 Email: pune@squarefoot.co.in

## **Area Representatives**

Bhopal	+91 82913 17558
Bhubaneshwar	+91 96742 23380
Coimbatore	+91 90032 56718
Guwahati	+91 96749 93005
Nasik	+91 86575 03355
Patna	+91 98363 11556
Surat	+91 97237 77887



## **Head Office:**

Classic Floorings & Interiors (P) Ltd., Ground Floor, Raghuvanshi Mansion Raghuvanshi Mills Compound, 9–11 Senapati Bapat Marg, Lower Parel, Mumbai – 400 013. Tel: +91 22 4047 6211 | Fax: +91 22 2497 6216