



## STYLE ELLE XF2

Technical Data Sheet



THE ULTIMATE  
FLOORING EXPERIENCE



# WETROOM STYLE ELLE XF2

## Technical Data

CERTIFICATION & CLASSIFICATION	STANDARDS	Veneto xl <sup>TM</sup> 2 mm	Style Estima xl <sup>TM</sup> 1.5 mm	Linoleum xl <sup>TM</sup> B1 2.5 mm	Originale Essenza 2.5mm	Veneto Sicuro xl <sup>TM</sup> 2.5 mm	Etrusco xl <sup>TM</sup> 2.5 mm	Linoleum Conductive xl <sup>TM</sup> 2.5 mm	Linoleum SD Static Dissipative xl <sup>TM</sup> 2.5 mm	Veneto xl <sup>TM</sup> 3.0 mm	Silencio xl <sup>TM</sup> 3.0 mm	Veneto Acoustic Cork xl <sup>TM</sup> 4.4 mm	Unilin <sup>®</sup> 2 mm
Type of floor covering	ISO 24011 (EN 548)	EN 686	-	-	One single-layer calendared linoleum on jute backing	-	-	Conductive linoleum flooring	Static Dissipative linoleum flooring	One single-layer calendared linoleum on jute backing	-	-	Approved linoleum for walls application
CE certification	EN 14041	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	EN 15102
Classification	ENISO 10874 Domestic	Class: 23	Class: 23	Class: 23	Class: 23	Class: 23	Class: 23	Class: 23	Class: 23	Class: 23	Class: 23	Class: 23	Class: -
	ENISO 10874 Commercial	Class: 32	Class: 34	Class: 34	Class: 34	Class: 34	Class: 34	Class: 34	Class: 34	Class: 34	Class: 34	Class: 34	Class: -
	ENISO 10874 Light Industrial	Class: 41	Class: 43	Class: 43	Class: 43	Class: 43	Class: 43	Class: 43	Class: 43	Class: 43	Class: 41	Class: 42	Class: -
TECHNICAL CHARACTERISTICS	STANDARDS	xl <sup>TM</sup>	xl <sup>TM</sup>	xl <sup>TM</sup>	Essenza	xl <sup>TM</sup>	xl <sup>TM</sup>	xl <sup>TM</sup>	xl <sup>TM</sup>	xl <sup>TM</sup>	xl <sup>TM</sup>	xl <sup>TM</sup>	xl <sup>TM</sup>
Surface treatment	ENISO 24346	2.0 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm	3.2 mm	3.8 mm	4.4 mm	2.0 mm
Total thickness	ENISO 23997	ca. 2.400 g/m <sup>2</sup>	ca. 3.000 g/m <sup>2</sup>	ca. 3.200 g/m <sup>2</sup>	ca. 3.000 g/m <sup>2</sup>	ca. 3.000 g/m <sup>2</sup>	ca. 3.000 g/m <sup>2</sup>	ca. 3.000 g/m <sup>2</sup>	ca. 3.000 g/m <sup>2</sup>	ca. 3.900 g/m <sup>2</sup>	ca. 4.450 g/m <sup>2</sup>	ca. 4.600 g/m <sup>2</sup>	ca. 2.900 g/m <sup>2</sup>
Residual indentation	ENISO 24343-1 Standard requirements	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm	≤ 0.15 mm	≤ 0.30 mm	≤ 0.40 mm	-
Best measured value	ENISO 24343-1	ca. 0.07 mm	ca. 0.08 mm	ca. 0.08 mm	ca. 0.08 mm	ca. 0.08 mm	ca. 0.08 mm	ca. 0.08 mm	ca. 0.08 mm	ca. 0.20 mm	ca. 0.20 mm	ca. 0.20 mm	-
Flexibility	ENISO 24344 Method A	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	-
Form of delivery	ENISO 24341	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m or ≤ 32 x 1.95 m (subject to availability by-phase check upon order)	≤ 16 x 2 m
TECHNICAL PERFORMANCES	STANDARDS	Cp=1	Cp=1	Bp=1	Cp=1	Cp=1	Cp=1	Bp=1	Cp=1	Cp=1	Cp=1	Cp=1	B=2 dB
Fire classification	EN 13501-1	Cp=1	Cp=1	Bp=1	Cp=1	Cp=1	Cp=1	Bp=1	Cp=1	Cp=1	Cp=1	Cp=1	B=2 dB
Fire effluent toxicity	ISO 9697 (evaluation according to EN 6050-2 Annex C)	-	-	-	-	-	-	-	-	-	-	-	CTP(4mm) = 0.06 and CTG(8mm) = 0.09, testing with irradiance of 50 kW/m <sup>2</sup> without pilot flame
Impact sound reduction	ENISO 10140-3 / ENISO 1717-2	5 dB	6 dB	6 dB	6 dB	6 dB	6 dB	6 dB	6 dB	8 dB	10 dB	15 dB	-
Impact sound in the room	NF S31-074	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class B < 75 dB	Class A < 65 dB	Class B < 75 dB	-
Impact sound reduction with Eufonox <sup>®</sup>	ENISO 10140-3 / ENISO 1717-2	14 dB	14 dB	14 dB	14 dB	14 dB	14 dB	14 dB	14 dB	15 dB	15 dB	15 dB	-
Castor chair	ENISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)						Suitable for office chairs with castors type W (Norm EN 12529)					
Static electrical propensity	EN 1815	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV
Electrical resistance	EN 1081	-	-	-	-	-	-	R1 ≤ 10 <sup>10</sup> Ω	R1 ≤ 10 <sup>10</sup> Ω	-	-	-	-
ESD approval SP method	2472	-	-	-	-	-	-	R2 ≤ 10 <sup>10</sup> Ω	R2 ≤ 10 <sup>10</sup> Ω	-	-	-	-
ENEC 61340-4-1	-	-	-	-	-	-	-	R ≤ 10 <sup>10</sup> Ω	R ≤ 10 <sup>10</sup> Ω	-	-	-	-
Impact resistance	EN 259-2	-	-	-	-	-	-	-	-	-	-	-	Resistant to impacts
Slip resistance	EN 13893 DIN 51130	DS ≥ 0.30 / R9	DS ≥ 0.30 / R9	DS ≥ 0.30 / R9	DS ≥ 0.30 / R9	DS ≥ 0.30 / R9	DS ≥ 0.30 / R9	DS ≥ 0.30 / R9	DS ≥ 0.30 / R9	DS ≥ 0.30 / R9	DS ≥ 0.30 / R9	DS ≥ 0.30 / R9	-
Chemical resistance	ENISO 26987	Resistant to dilute acids, oils, fats, current solvents and alkalis						Resistant to dilute acids, oils, fats, current solvents and alkalis					
Thermal resistance Underfloor heating	ENISO 10456	0.012 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.015 m <sup>2</sup> K/W Suitable	0.019 m <sup>2</sup> K/W Suitable	0.042 m <sup>2</sup> K/W Suitable	0.045 m <sup>2</sup> K/W Suitable	0.018 m <sup>2</sup> K/W Suitable
Light fastness	ENISO 105-B02	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6
Presence of phthalate compounds	CEN RO/TS 16181	Phthalate free						Phthalate free					
Odor test requirement of emission class M1	VCI 4302	Meets requirement						Meets requirement					
Spillage, availability and extra washability	EN 13356 EN 233	-	-	-	-	-	-	-	-	-	-	-	Extra washable
Determination of antibacterial activity	ISO 22196	Naturally bactericidal (Bacteria mix - E-Coli and MRSA)						Naturally bactericidal (Bacteria mix - E-Coli and MRSA)					
Colours	19	60 (Veneto) 13 (Style Estima) 8 (Silencio) 10 (Trentino)	ON REQUEST: 60 (Veneto) 8 (Style Estima) 13 (Style Estima) 16 (Etrusco) 10 (Trentino) 3 (Originale Vegetale) 3 (Originale Minerale)	29 (Veneto) 8 (Style Estima) 13 (Style Estima) 16 (Etrusco) 10 (Trentino) 3 (Originale Vegetale) 3 (Originale Minerale)	ON REQUEST: 60 (Veneto)	16	1	3	9	27 (Veneto) 8 (Style Estima) 13 (Style Estima) 16 (Etrusco) 10 (Trentino)	ON REQUEST: 60 (Veneto)	6	

The above information is subject to modification for the benefit of further improvement (DIT).

**DISCLAIMER:** Although the utmost care is taken, the data here given could differ and be subject to modifications from a technical point of view. We do not accept responsibility for color variations. Tarkett reserves the right to modify its technical specifications, colors and materials at any moment and without prior notice. Please check the effective availability of the products presented at the time of order. Due to the technical limits of reproduction and printing techniques used, the appearance (color) of the product may vary from the samples, panels or other visual display materials exhibited to the customer. It is mandatory to have the products installed properly if they are to be service comply and safely. Refer to Tarkett technical installation and maintenance directions, available at [www.tarkett.com](http://www.tarkett.com) or at your Tarkett dealer. \*Eufonox: 2.0mm traditional, 100% natural corkstone underlayment to be installed in combination with any compact Tarkett linoleum to get additional sound reduction up to 15dB, depending on the product. Available in rolls 32m x 2m.

CUSTOMS TARIFF: 482050000000F



Lineoleum xl <sup>TM</sup> SD	Linoleum Conductive xl <sup>TM</sup> 2.5mm	Lineoleum xl <sup>TM</sup> 2.0mm	Etrusco xl <sup>TM</sup>	Style Estima xl <sup>TM</sup>	Originale Vegetale 2.5mm	Originale Minerale 2.5mm	Trentino xl <sup>TM</sup> 2.5 mm	Silencio xl <sup>TM</sup> 3.0 mm	Veneto xl <sup>TM</sup> 2 mm	Veneto xl <sup>TM</sup> 2.5 mm	Veneto xl <sup>TM</sup> 3.2 mm	Linoleum xl <sup>TM</sup> B1 2.5 mm	Veneto Essenza 2.5 mm
CE 0200-0141-2404-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0141-2404-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0145-0420-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0439-0430-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0442-0420-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0450-0430-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0450-0430-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0444-0420-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0440-0420-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0141-2404-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0141-2404-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0141-2404-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0141-2404-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY	CE 0200-0141-2404-2011-1407 http://professional.tarkett.com Manufactured by Tarkett SA 05036 Narni - ITALY

Acoustic Cork	Conductive	Eufonox	Etrusco	Originale	SD	Silencio	Style	Trentino	Veneto
93% Natural Cork	96% Natural Cork	100% Natural Cork	93% Natural Cork	99% Natural Cork	98% Natural Cork	83% Natural Cork	96% Natural Cork	94% Natural Cork	94% Natural Cork
77% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free
Optimal Indoor Air Quality	Optimal Indoor Air Quality	Optimal Indoor Air Quality	Optimal Indoor Air Quality	Optimal Indoor Air Quality	Optimal Indoor Air Quality	Optimal Indoor Air Quality	Optimal Indoor Air Quality	Optimal Indoor Air Quality	Optimal Indoor Air Quality

### SUSTAINABILITY

Tarkett was the first linoleum flooring manufacturer to be Cradle to Cradle® certified - underlining our strong commitment to sustainability.

### Product certifications



Originale Essenza and Veneto Essenza 100% linen. All our linoleum ranges (except SD Static Dissipative and Linoleum Conductive xl<sup>TM</sup> ranges).

### International certifications



### Factory certifications



All our linoleum products are eligible for LEED v4 credits. For more information: <http://www.c2certified.org/products/registry>

Data is subject to change.

**Ahmadabad:**

Surface Plus, GF, 4th Floor  
Premier House, Opp. Gurudwara  
Thaltej Crossing, Ahmadabad – 382 454  
Tel: +91 79 4006 0521 / 79 2685 3312  
Email: ahmadabad@squarefoot.co.in

**Bengaluru:**

#51, 1st Floor, 100 Feet Road  
4th Block, Koramangala  
Bengaluru – 560 034  
Tel: +91 80 4110 1012 / 13  
Fax: +91 80 2563 3145  
Email: bangalore@squarefoot.co.in

**Chennai:**

#96, 3rd Floor, Opp. Vani Mahal  
G. N. Chetty Road, T. Nagar  
Chennai – 600 017  
Tel: +91 44 4550 8411 / 12  
Email: chennai@squarefoot.co.in

**Goa:**

403, 4th Floor, Gera Imperium  
1st Building, Behind KTC Bus Stand  
Patto Plaza, Panjim, Goa – 403 001  
Tel: +91 832 243 7663  
Email: goa@squarefoot.co.in

**Hyderabad:**

6 – 3 – 354/1, 2nd Floor, Stellar Sphinx  
Panjagutta Main Road, Road No. 1  
Banjara Hills, Hyderabad – 500 034  
Tel: +91 40 4003 7212 / 13  
Fax: +91 40 4003 7214  
Email: hyderabad@squarefoot.co.in

**Indore:**

154, 1st Floor Orbit Mall, A.B. Road  
Indore – 452 001  
Tel: +91 731 498 1983  
Email: indore@squarefoot.co.in

**Jaipur:**

2nd Floor, Plot No. 287, Vaishali Marg  
Gomes Defence Colony, Opp. Ktl Maruti Showroom  
Near Big Bazaar, Jaipur, Rajasthan – 302 021  
Tel: +91 141 492 2396  
Email: jaipur@squarefoot.co.in

**Kochi:**

2nd Floor Chakrampilly Estate  
NH Bypass, Palarivattom  
Thammanam PO, Cochin  
Kerala – 682 032. (Opp: Holiday Inn)  
Tel: +91 484 485 6173  
Email: kochi@squarefoot.co.in

**Kolkata:**

#332, Homeland Mall  
18B, Ashuthosh Mukherjee Road  
Kolkata – 700 020  
Tel: +91 33 2455 4344  
Email: kolkata@squarefoot.co.in

**Mumbai:**

9–11 Senapati Bapat Marg  
Lower Parel, Mumbai – 400 013  
Tel: +91 22 4047 6211  
Fax: +91 22 2497 6216

**New Delhi:**

M – 56, 2nd Floor, M–Block Market  
Greater Kailash Part II  
New Delhi – 110 048  
Tel: +91 11 4052 5767 / 11 4050 4785  
Email: delhi@squarefoot.co.in

**Pune:**

Classic Floorings & Interiors Pvt Ltd,  
Office No. 201, 2nd Floor, Gagan Capital  
Dhole Patil Road, Beside Ruby hall Clinic Exit Gate,  
Landmark – Above Anna Idly & CCD  
Pune – 411 001  
Tel: +91 20 4000 1630  
Email: pune@squarefoot.co.in

**Area Representatives**

Bhopal	+91 82913 17558
Bhubaneshwar	+91 96742 23380
Coimbatore	+91 90032 56718
Guwahati	+91 96749 93005
Nasik	+91 86575 03355
Patna	+91 98363 11556
Surat	+91 97237 77887

**Head Office:**

Classic Floorings & Interiors (P) Ltd., Ground Floor, Raghuvanshi Mansion  
Raghuvanshi Mills Compound, 9–11 Senapati Bapat Marg, Lower Parel, Mumbai – 400 013. Tel: +91 22 4047 6211 | Fax: +91 22 2497 6216

Toll Free: 1800 226 211 ■ sales@squarefoot.co.in ■ www.squarefoot.co.in