



STYLE EMME XF2

Technical Data Sheet



THE ULTIMATE
FLOORING EXPERIENCE



WETROOM STYLE EMME XF2

Technical Data

CERTIFICATION & CLASSIFICATION	STANDARDS	Veneto 10 ^{mm}	Style Emme 11 ^{mm}	Lineum of 11 ^{mm} B x 2,5 mm	Originele Essenza 2,5mm	Venetico Scuro 4 ^{mm} 2,5 mm	Etrusco 4 ^{mm} 2,5 mm	Lineum Conductive of 2,5 mm	Lineum SD Static Dissipative of 2,5 mm	Nero 4 ^{mm} 3,5 mm	Mirolo 4 ^{mm} 3,8 mm	Nero Acoustic Cork of 4,4 mm	Lineum 11 ^{mm}
ISO 24011 (EN 548)				One single-layer calendared linoleum on jute backing				Conductive linoleum flooring		Static Dissipative linoleum flooring		One single-layer calendared linoleum on jute backing	Approved linoleum for walls application
Type of floor covering	EN 686 EN 687	-	-	-	-	-	-	-	-	-	-	-	-
CE certification	EN 14041 EN ISO 10874 Domestic Commercial Light Industrial	Yes Class 23 23 23 23 41	Yes Class 23 23 23 23 43	Yes Class 23 23 23 23 43	Yes Class 23 23 23 23 43	Yes Class 23 23 23 23 43	Yes Class 23 23 23 23 43	Yes Class 23 23 23 23 43	Yes Class 23 23 23 23 43	Yes Class 23 23 23 23 43	Yes Class 23 23 23 23 43	Yes Class 23 23 23 23 42	Yes Class 23 23 23 23 42
TECHNICAL STANDARDS													
Surface treatment		sf**	sf**	sf**	Essenza	sf**	sf**	sf**	sf**	sf**	sf**	sf**	sf**
Total thickness	EN ISO 24346	2,0 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	2,5 mm	3,2 mm	3,8 mm	2,0 mm
Total weight	EN ISO 23997	ca. 2.400 g/m ²	ca. 3.000 g/m ²	ca. 3.200 g/m ²	ca. 3.000 g/m ²	ca. 3.000 g/m ²	ca. 3.000 g/m ²	ca. 3.000 g/m ²	ca. 3.000 g/m ²	ca. 3.900 g/m ²	ca. 3.450 g/m ²	ca. 4.600 g/m ²	ca. 2.900 g/m ²
Residual indentation	EN ISO 24343-1	Standard requirements Best measured value	≤ 0,15 mm ca. 0,07 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,15 mm ca. 0,08 mm	≤ 0,30 mm ca. 0,20 mm	≤ 0,40 mm ca. 0,32 mm
Flexibility	EN ISO 24344 Method A	≤ 25 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø
Form of delivery	EN ISO 24341	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m or ≤ 32 x 1,95 m (subject to availability by phase check upon order)	≤ 16 x 2 m
TECHNICAL PERFORMANCE STANDARDS													
Fire classification	EN 13501-1	Cp+1	Cp+1	Bp+1	Cp+1	Cp+1	Cp+1	Bp+1	Cp+1	Cp+1	Cp+1	Cp+1	B+2
Fire efficient toxicity	ISO 9697 evaluation according to EN ISO 505-2 Annex C1	-	-	-	-	-	-	-	-	-	-	-	-
Impact sound reduction	EN ISO 10140-3 EN ISO 717-2	5 dB	6 dB	6 dB	6 dB	6 dB	6 dB	6 dB	6 dB	6 dB	8 dB	10 dB	15 dB
Impact sound in the room	ISO 717-2	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class B < 75 dB	Class A < 65 dB	Class B < 75 dB	Class B < 75 dB
Impact sound reduction with Eufono®	EN ISO 10140-3 EN ISO 717-2	14 dB	14 dB	14 dB	14 dB	14 dB	14 dB	14 dB	14 dB	15 dB	15 dB	15 dB	15 dB
Castor chair	EN ISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)							Suitable for office chairs with castors type W (Norm EN 12529)				
Static electrical propensity	EN 1815	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV
Electrical resistance	EN 1081 ESD approval SP method 2472 EN IEC 61340-4	-	-	-	-	-	-	R1 ≤ 10 ¹⁰ R2 ≤ 10 ¹⁰ R ≤ 10 ¹⁰ R ≤ 10 ¹⁰	R1 ≤ 10 ¹⁰ R2 ≤ 10 ¹⁰ R ≤ 10 ¹⁰ R ≤ 10 ¹⁰	-	-	-	-
Impact resistance	EN 259-2	-	-	-	-	-	-	-	-	-	-	-	Resistant to impacts
Slip resistance	EN 13893 EN 15120	DS ≥ 0,30 RS	DS ≥ 0,30 RS	DS ≥ 0,30 RS	DS ≥ 0,30 RS	DS ≥ 0,30 RS	DS ≥ 0,30 RS	DS ≥ 0,30 RS	DS ≥ 0,30 RS	DS ≥ 0,30 RS	DS ≥ 0,30 RS	DS ≥ 0,30 RS	DS ≥ 0,30 RS
Chemical resistance	EN ISO 24687	Resistant to dilute acids, oils, fats, current solvents and alkalis							Resistant to dilute acids, oils, fats, current solvents and alkalis				
Thermal resistance	EN ISO 10456	0,012 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,015 m ² K/W Suitable	0,019 m ² K/W Suitable	0,019 m ² K/W Suitable	0,042 m ² K/W Suitable	0,045 m ² K/W Suitable
Light fastness	EN ISO 105-B02	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6
Presence of phthalate compounds	CEN EN/TS 16181	Phthalate free							Phthalate free				
Odor test requirement of emission class M1	EN ISO 16000-3 I.A. VCI 4102	Meets requirement							Meets requirement				
Spaciousness, availability and extra washability	EN ISO 23556 EN 233	-	-	-	-	-	-	-	-	-	-	-	Extra washable
Determination of antibacterial activity	ISO 22196	Naturally bactericidal (Bacteria mix - E-Coli and MRSA)							Naturally bactericidal (Bacteria mix - E-Coli and MRSA)				
Colours		19	60 (Veneto) 13 (Style Emme) (8 (Style Emme) 10 (Trentino)) ON REQUEST: 8 (Style Emme B) 9 (Style Emme B) 16 (Etrusco B) 10 (Trentino B)	29 (Veneto) 3 (Originele Vegetale) ON REQUEST: 60 (Veneto)	16	1	3	9		27 (Veneto) 8 (Style Emme) 1 (Style Emme) 3 (Etrusco) ON REQUEST: 10 (Trentino)	ON REQUEST: 60 (Veneto)	6	

The above information is subject to modification for the benefit of further improvement (DIT).
DISCLAIMER: Although the almost exact data is taken, the data here given could differ and be subject to modifications from a technical point of view.
 It is the customer's responsibility to check the technical specifications, colours and any other information at any moment and without prior notice. Please check the effective availability of the products presented at the time of order. Due to the technical limits of reproduction and printing techniques used, the appearance (colour) of the product may vary from the samples, panels or other visual display materials exhibited to the customer. It is mandatory to have the products installed properly if they are to be service comply and safely. Refer to Tarkett technical installation and maintenance directions, available at www.tarkett.com or at your Tarkett dealer.
 *Eufono: 20mm traditional, 100% natural corkstone underlayment to be installed in combination with any compact Tarkett linoleum to get additional sound reduction up to 15dB, depending on the product. Available in rolls 32m.

CUSTOMS TARIFF: 482050000000F



Product	CE Mark	Lineum Conductive 2,5mm	Lineum of 2,5mm	Style Emme 11	Originele Essenza 2,5mm	Originele Mirolo 3,8mm	Originele Mirolo 2,5mm	Trentino 11 2,5 mm	Silenzio 11 2,5 mm	Veneto 11 2,5 mm	Veneto 11 2,5 mm	Style 11 2,5 mm	Lineum of B x 2,5 mm	Silenzio 11 2,5 mm	Veneto Essenza 2,5 mm
Acoustic Cork	93% sound reduction	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free
Conductive	96% sound reduction	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free
Eufono	100% sound reduction	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free
Etrusco	93% sound reduction	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free
Originele	99% sound reduction	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free
SD	98% sound reduction	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free
Silenzio	83% sound reduction	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free
Style	96% sound reduction	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free
Trentino	94% sound reduction	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free
Veneto	94% sound reduction	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free	100% Phthalate Free

SUSTAINABILITY

Tarkett was the first linoleum flooring manufacturer to be Cradle to Cradle® certified - underlining our strong commitment to sustainability.

Product certifications

Cradle to Cradle GOLD
 Originele Essenza and Veneto Essenza 100% linen

Cradle to Cradle SILVER
 All our linoleum ranges (except SD Static Dissipative of and Lineum Conductive 4^{mm} ranges)

International certifications

EMERSONS DANS L'AIR INTERIEUR (A+, A, B, C)
 floor score
 EPD
 Declare

Factory certifications

Tarkett ISO 9001
 Tarkett ISO/TS 14067
 Tarkett ISO 50001
 Tarkett OHSAS 18001
 Tarkett ISO 14001
 Tarkett SA 8000

All our linoleum products are eligible for LEED v4 credits.
 For more information: <http://www.c2certified.org/products/registry>

Ahmadabad:

Surface Plus, GF, 4th Floor
Premier House, Opp. Gurudwara
Thaltej Crossing, Ahmadabad – 382 454
Tel: +91 79 4006 0521 / 79 2685 3312
Email: ahmadabad@squarefoot.co.in

Bengaluru:

#51, 1st Floor, 100 Feet Road
4th Block, Koramangala
Bengaluru – 560 034
Tel: +91 80 4110 1012 / 13
Fax: +91 80 2563 3145
Email: bangalore@squarefoot.co.in

Chennai:

#96, 3rd Floor, Opp. Vani Mahal
G. N. Chetty Road, T. Nagar
Chennai – 600 017
Tel: +91 44 4550 8411 / 12
Email: chennai@squarefoot.co.in

Goa:

403, 4th Floor, Gera Imperium
1st Building, Behind KTC Bus Stand
Patto Plaza, Panjim, Goa – 403 001
Tel: +91 832 243 7663
Email: goa@squarefoot.co.in

Hyderabad:

6 – 3 – 354/1, 2nd Floor, Stellar Sphinx
Panjagutta Main Road, Road No. 1
Banjara Hills, Hyderabad – 500 034
Tel: +91 40 4003 7212 / 13
Fax: +91 40 4003 7214
Email: hyderabad@squarefoot.co.in

Indore:

154, 1st Floor Orbit Mall, A.B. Road
Indore – 452 001
Tel: +91 731 498 1983
Email: indore@squarefoot.co.in

Jaipur:

2nd Floor, Plot No. 287, Vaishali Marg
Gomes Defence Colony, Opp. Ktl Maruti Showroom
Near Big Bazaar, Jaipur, Rajasthan – 302 021
Tel: +91 141 492 2396
Email: jaipur@squarefoot.co.in

Kochi:

2nd Floor Chakrampilly Estate
NH Bypass, Palarivattom
Thammanam PO, Cochin
Kerala – 682 032. (Opp: Holiday Inn)
Tel: +91 484 485 6173
Email: kochi@squarefoot.co.in

Kolkata:

#332, Homeland Mall
18B, Ashuthosh Mukherjee Road
Kolkata – 700 020
Tel: +91 33 2455 4344
Email: kolkata@squarefoot.co.in

Mumbai:

9–11 Senapati Bapat Marg
Lower Parel, Mumbai – 400 013
Tel: +91 22 4047 6211
Fax: +91 22 2497 6216

New Delhi:

M – 56, 2nd Floor, M–Block Market
Greater Kailash Part II
New Delhi – 110 048
Tel: +91 11 4052 5767 / 11 4050 4785
Email: delhi@squarefoot.co.in

Pune:

Classic Floorings & Interiors Pvt Ltd,
Office No. 201, 2nd Floor, Gagan Capital
Dhole Patil Road, Beside Ruby hall Clinic Exit Gate,
Landmark – Above Anna Idly & CCD
Pune – 411 001
Tel: +91 20 4000 1630
Email: pune@squarefoot.co.in

Area Representatives

Bhopal	+91 82913 17558
Bhubaneshwar	+91 96742 23380
Coimbatore	+91 90032 56718
Guwahati	+91 96749 93005
Nasik	+91 86575 03355
Patna	+91 98363 11556
Surat	+91 97237 77887

**Head Office:**

Classic Floorings & Interiors (P) Ltd., Ground Floor, Raghuvanshi Mansion
Raghuvanshi Mills Compound, 9–11 Senapati Bapat Marg, Lower Parel, Mumbai – 400 013. Tel: +91 22 4047 6211 | Fax: +91 22 2497 6216

Toll Free: 1800 226 211 ■ sales@squarefoot.co.in ■ www.squarefoot.co.in



Linoleum xf 2 SD
 0200-0017-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Linoleum Conductive xf 2 2.5 mm
 0200-0041-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

LinoWall xf 2 2 mm
 0200-0045-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 15102:2007+A1:2011

Etrusco xf 2
 0200-0020-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Style Emme xf 2
 0200-0034-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Style Elle xf 2
 0200-0031-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Originale Vegetale 2.5mm
 0200-0050-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Originale Minerale 2.5mm
 0200-0047-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Trentino xf 2 2.5 mm
 0200-0043-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Silencio xf 2 3.8 mm
 0200-0027-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Veneto xf 2 2 mm
 0200-0010-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Veneto xf 2 2.5 mm
 0200-0001-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Veneto xf 2 3.2 mm
 0200-0012-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Linoleum xf 2 B 2.5 mm
 0200-0014-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Veneto Sicuro xf 2
 0200-0005-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Veneto Essenza 2,5 mm
 0200-0011-DoP-2013-07
<http://professionals.tarkett.com>
 Manufactured by TarkettSpA
 05036 Narni - ITALY
 EN 14041:2004

Acoustic
Cork

93 %
77%
Natural
Renewable

100 %
33 %
Recyclable
Recycled content

PHTHALATE
FREE

≤10µg/m³
Optimal Indoor
Air Quality
*TVOC AT 28 DASy

Conductive

96 %
58%
Natural
Renewable

100 %
18 %
Recyclable
Recycled content

PHTHALATE
FREE

≤10µg/m³
Optimal Indoor
Air Quality
*TVOC AT 28 DASy

Elafono

100 %
85%
Natural
Renewable

100 %
34 %
Recyclable
Recycled content

PHTHALATE
FREE

≤10µg/m³
Optimal Indoor
Air Quality
*TVOC AT 28 DASy

Etrusco

93 %
77%
Natural
Renewable

100 %
34 %
Recyclable
Recycled content

PHTHALATE
FREE

≤10µg/m³
Optimal Indoor
Air Quality
*TVOC AT 28 DASy

Originale

99 %
80%
Natural
Renewable

100 %
30 %
Recyclable
Recycled content

PHTHALATE
FREE

≤10µg/m³
Optimal Indoor
Air Quality
*TVOC AT 28 DASy

SD

98 %
58%
Natural
Renewable

100 %
18 %
Recyclable
Recycled content

PHTHALATE
FREE

≤10µg/m³
Optimal Indoor
Air Quality
*TVOC AT 28 DASy

Silencio

83 %
65%
Natural
Renewable

100 %
40 %
Recyclable
Recycled content

PHTHALATE
FREE

≤10µg/m³
Optimal Indoor
Air Quality
*TVOC AT 28 DASy

Style

96 %
74%
Natural
Renewable

100 %
30 %
Recyclable
Recycled content

PHTHALATE
FREE

≤10µg/m³
Optimal Indoor
Air Quality
*TVOC AT 28 DASy

Trentino

94 %
76%
Natural
Renewable

100 %
36 %
Recyclable
Recycled content

PHTHALATE
FREE

≤10µg/m³
Optimal Indoor
Air Quality
*TVOC AT 28 DASy

Veneto

94 %
76%
Natural
Renewable

100 %
36 %
Recyclable
Recycled content

PHTHALATE
FREE

≤10µg/m³
Optimal Indoor
Air Quality
*TVOC AT 28 DASy