



Ecofit is a new hybrid indoor flooring with a stone core. It comes with a glue less locking system and can be used extensively in all residential and commercial areas. The product needs no maintenance and comes with a 15 year guarantee! Enjoy your wooden flooring without having to worry about water problems ever!

TECHNICAL CHARACTERISTICS	STANDARDS	EcoFit
Abrasion/Wear Resistance	EN 16511	0.3mm wear layer > 1500 cycles; Class 31, Heavy domestic & Moderate commercial 0.5mm wear layer > 5000 cycles; Class 33, Heavy commercial
Scratch	-	3000g Pass
Peel resistance	-	Length direction: 125N/50mm Width direction: 140N/50mm Pass
Residual indentation	EN 16511	< 0.15mm, 0.02 Class 34, Very Heavy commercial
Impact resistance	EN 16511	≥1800mm Class 34, Very Heavy commercial
Slip resistance	EN 14041 -	0.37, Class DS
Color fastness to light	EN 13329	
Resistance to staining	EN 16511	Group 1 and 2: Grade 5, Group3: Grade 4 Class 34, Very Heavy commercial
Dimensional stability & curling	EN 16511	Length direction: 0.08% Width direction: - 0.02% Curling: 0.03mm Class 34, Very Heavy commercial
Water resistance/ Swelling in water	EN 16511	0.20% Class 34, Very Heavy commercial
Locking strength	EN 16511	Long side: 4.9KN/m Short side: 4.2KN/m Class 34, Very Heavy commercial
Thermal conductivity	EN 14041	0.126 W/(m.k) Suitable for underfloor heating system
Thermal resistance	EN 14041	0.030 m²-K/W Suitable for underfloor heating system
Reaction to fire	EN 14041	Class B _f s1
Formaldehyde emission	EN 14041	0.005mg/m³ E1
VOC	Decret No2011-321 Floorscore	Non Detected - A+ Non Detected, Floorscore certified
Lead	CPSIA	Non Detected Meet children toy regulation
PCP	EN 14041	Non Detected, Pass
Phthalate content	-	Non Detected, Pass
Substances of Very High Concern (SVHC)	EU REACH regulation No. 1907/2006	Non Detected, REACH compliant
The body Voltage	-	0.4 KV, Pass
Castor Chair	EN 16511	≥ 25000 cirlces Class 34, Very Heavy commercial
Dimensions	-	Plank - 4 X 181 X 1220mm Tile - 610 X 305 X 4mm 760 X 465 X 4/0.5mm
Packing Per box	-	Plank - 2.65 sqmtr Tile - 2.60 sqmtr 2.83 sqmtr







Ahmadabad:

Surface Plus, GF, 4th Floor **Premier House** Opp. Gurudwara Thaltej Crossing Ahmadabad - 382 454

Tel: +91 79 4006 0521 / 78782 10126

Bengaluru:

#51, 1st Floor, 4th Block 100 Feet Road, Koramangala Bengaluru - 560 034 Tel: +91 80 4110 1012 / 13 Fax: +91 80 2563 3145

Chennai:

Nawazish Building, 2nd Floor No.30, Khader Nawaz Khan Road Nungambakkam Chennai - 600 006 Tel: +91 44 4550 8411 / 4550 8412

Goa:

605 Gera Imperium Patto Plaza. B/H KTC Bus Stand Panjim. Goa - 403 001 Tel: +91 832 243 7663

Hyderabad:

302, 3rd Floor, Whiterock Square Building, 1-62 / 122 Plot No. 122 Block-B of Kavuri Hills Guttala Begumpet Village Under GHMC Serilingampally Mandal Hyderabad - 500 033. Ranga Reddy District Tel: +91 40 4003 7212 / 13

Jaipur:

2nd Floor, Plot No. 287 Vaishali Marq Gomes Defence Colony Opp. Ktl Maruti Showroom Near Big Bazaar Jaipur, Rajasthan – 302 021 Tel: +91 141 492 2396 / 82919 52996

Kochi:

2nd Floor Chakrampilly Estate NH Bypass, Palarivattom, Opp: Holiday Inn Thammanam P.O, Cochin, Kerala – 682 032 Tel: +91 484 485 6173

Kolkata:

34, Dr.Sarat Banerjee Road Police Station: Rabindra Sarobar BSNL Telephone Exchange Lane Kolkata - 700 029 Tel: +91 33 4060 4243

New Delhi:

A-32, 3rd Floor FIEE Complex, Okhla Phase-II New Delhi - 110 020 Tel: +91 11 4052 5767

Pune:

201 Gagan Capital, 2nd Floor **Dhole Patil Road** Beside Exit Gate of Ruby Hall Clinic Above Anna Idly, Pune - 411 001 Tel: +91 20 400 1630

Area Representatives

Bhopal +91 82913 17558 Indore +91 73149 81983 Guwahati +91 97486 65777 Patna +91 97714 17980 Surat +91 78782 10126



Head Office:

Classic Floorings & Interiors (P) Ltd., Ground Floor, Raghuvanshi Mansion Raghuvanshi Mills Compound, 9-11 Senapati Bapat Marg, Lower Parel, Mumbai - 400 013. Tel: +91 22 4047 6211 | Fax: +91 22 2497 6216